

# ROUND SLING

## SPECIFICATION FOR 10 TONNE - ORANGE

AS  
4497.1



### Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling.

Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank.

Conforms to Australian Standard AS 4497.1.

Black colour available upon request.

### Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.

**WLL 10000KG**

#### WLL 10000KG ORANGE

CODE	LENGTH (M)	Wt. (kg)
901010	1.0	2.2
901015	1.5	3.03
901020	2.0	3.3
901025	2.5	4.2
901030	3.0	5
901035	3.5	5.98
901040	4.0	7.98
901045	4.5	8.08
901050	5.0	10.51
901055	5.5	9.896
901060	6.0	11.98
901080	8.0	17
901100	10.0	19.87



#### WORKING LOAD LIMITS CHART (KG) - (WLLs)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
ORANGE	10000	8000	20000	17000	14000	10000	13,800	13,800