

ROUND SLING

SPECIFICATION FOR 12 TONNE - ORANGE



Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank. Conforms to Australian Standard AS 4497.1. Black colour available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

WLL 12,000KG

| WLL 12000KG ORANGE | | |
|--------------------|------------|----------|
| CODE | LENGTH (M) | Wt. (kg) |
| 901230 | 3.0 | 7.5 |
| 901240 | 4.0 | 9.37 |
| 901250 | 5.0 | 12.3 |
| 901260 | 6.0 | 14.76 |
| 901280 | 8.0 | 16.03 |
| 901291 | 10.0 | 22.45 |
| 901292 | 12.0 | 28.5 |

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.



WORKING LOAD LIMITS CHART (KG) - (WLLs)

| ROUND SLING | | | | | | | | |
|-------------|----------|-------|--------|-------|-------|-------|------------------------|------------------------|
| | VERTICAL | CHOKE | BASKET | 60° | 90° | 120° | SINGLE WRAP Max 45° | DOUBLE WRAP Max 45° |
| ORANGE | 12000 | 9600 | 24000 | 20400 | 16800 | 12000 | 16,560 | 16,560 |

NSW Head Office

🏠 43 Frank Street
 Wetherill Park, NSW 2164
 ☎ 02 9757 2277

WA Office

🏠 42 Mulgool Road
 Malaga, WA 6090
 ☎ 08 9248 6674

QLD Office

🏠 7 Durbell Street
 Acacia Ridge, QLD 4110
 ☎ 07 3272 0777

VIC Office

🏠 47 Technology Drive
 Sunshine West, VIC 3020
 ☎ 03 9314 5525