

ROUND SLING



Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank. Conforms to Australian Standard AS 4497.1. Black colour available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.

WLL 15,000KG

WLL 15000KG ORANGE		
CODE	LENGTH (M)	Wt. (kg)
901520	2.0	6.75
901540	4.0	13.5
901560	6.0	19
901580	8.0	27
901591	10.0	34
901592	12.0	46



WORKING LOAD LIMITS CHART (KG) - (WLLs)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
ORANGE	15000	12000	30000	25500	21000	15000	20,700	20,700

NSW Head Office

📍 43 Frank Street
 Wetherill Park, NSW 2164
 ☎ 02 9757 2277

WA Office

📍 42 Mulgool Road
 Malaga, WA 6090
 ☎ 08 9248 6674

QLD Office

📍 7 Durbell Street
 Acacia Ridge, QLD 4110
 ☎ 07 3272 0777

VIC Office

📍 47 Technology Drive
 Sunshine West, VIC 3020
 ☎ 03 9314 5525