

FLAT WEB SLING

SPECIFICATION FOR 1 TONNE - VIOLET

AS
1353.1



WLL 1000KG

VIOLET WIDTH: 50mm

CODE	LENGTH (M)	Wt. (kg)
910105	0.5	0.25
910110	1.0	0.45
910115	1.5	0.6
910120	2.0	0.72
910125	2.5	0.85
910130	3.0	0.98
910135	3.5	0.94
910140	4.0	1.25
910145	4.5	1.49
910150	5.0	1.50
910155	5.5	1.6
910160	6.0	1.72
910170	7.0	1.96
910180	8.0	2.2
910190	9.0	2.44
910191	10.0	2.68

Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

Note: Other variations available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing



WORKING LOAD LIMITS CHART (KG) - (WLLs)

FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
VIOLET	1000	800	2000	1700	1400	1000	1700	1400