

# ROUND SLING

## SPECIFICATION FOR 20 TONNE - ORANGE



### Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank. Conforms to Australian Standard AS 4497.1. Black colour available upon request.

### Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.

## WLL 20,000KG

WLL 20000KG ORANGE		
CODE	LENGTH (M)	Wt. (kg)
902010	1.0	5
902015	1.5	7.8
902020	2.0	10.5
902025	2.5	11
902030	3.0	15
902040	4.0	23
902045	4.5	23.62
902050	5.0	26.25
902060	6.0	31.5
902080	8.0	42
902100	10.0	52.5
902120	12.0	63



### WORKING LOAD LIMITS CHART (KG) - (WLLs)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
ORANGE	20000	16000	40000	34000	28000	20000	27,600	27,600

**NSW Head Office**

🏠 43 Frank Street  
 Wetherill Park, NSW 2164  
 ☎ 02 9757 2277

**WA Office**

🏠 42 Mulgool Road  
 Malaga, WA 6090  
 ☎ 08 9248 6674

**QLD Office**

🏠 7 Durbell Street  
 Acacia Ridge, QLD 4110  
 ☎ 07 3272 0777

**VIC Office**

🏠 47 Technology Drive  
 Sunshine West, VIC 3020  
 ☎ 03 9314 5525