

# FLAT WEB SLING

## SPECIFICATION FOR 2 TONNE - GREEN

**AS  
1353.1**



**WLL 2000KG**

GREEN WIDTH: 60mm		
CODE	LENGTH (M)	Wt. (kg)
910205	0.5	0.3
910210	1.0	0.62
910215	1.5	0.84
910220	2.0	1.06
910225	2.5	1.25
910230	3.0	1.4
910235	3.5	1.62
910240	4.0	1.86
910245	4.5	2.3
910250	5.0	2.16
910255	5.5	2.38
910260	6.0	2.6
910270	7.0	3.05
910280	8.0	3
910290	9.0	3.8
910291	10.0	4.2

### Flat Web Sling - Polyester

Every Austlift flat webbing sling is fabricated using 100% high tenacity polyester yarn. Durable and specially woven, 100% polyester with standard folded eyes that incorporates eye wear padding to provide maximum protection around the eyes.

Each sling is proof tested, individually serial numbered, tagged and complete with test certificates.

Manufactured to the specifications of Austlift and according to Australian Standard AS1353.1.

Note: Other variations available upon request.

### Application









- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 8 x the load indicated
- 2 Ply webbing



WORKING LOAD LIMITS CHART (KG) - (WLLs)

FLAT WEBBING SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	60°	60° CHOKE
GREEN	2000	1600	4000	3400	2800	2000	3400	2800