

ROUND SLING

SPECIFICATION FOR 2 TONNE - GREEN

AS
4497.1



Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling.

Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank.

Conforms to Australian Standard AS 4497.1.

Black colour available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.

WLL 2000KG

WLL 2000KG GREEN

| CODE | LENGTH(M) | Wt. (kg) |
|--------|-----------|----------|
| 900205 | 0.5 | 0.27 |
| 900207 | 0.7 | 0.26 |
| 900210 | 1.0 | 0.47 |
| 900215 | 1.5 | 0.75 |
| 900220 | 2.0 | 0.97 |
| 900225 | 2.5 | 1.11 |
| 900230 | 3.0 | 1.21 |
| 900235 | 3.5 | 1.38 |
| 900240 | 4.0 | 1.55 |
| 900245 | 4.5 | 1.72 |
| 900250 | 5.0 | 2.18 |
| 900260 | 6.0 | 2.58 |
| 900270 | 7.0 | 2.98 |
| 900280 | 8.0 | 3.96 |
| 900291 | 10.0 | 4.3 |



WORKING LOAD LIMITS CHART (KG) - (WLLs)

| ROUND SLING | | | | | | | | |
|-------------|----------|-------|--------|------|------|------|------------------------|------------------------|
| | VERTICAL | CHOKE | BASKET | 60° | 90° | 120° | SINGLE WRAP Max 45° | DOUBLE WRAP Max 45° |
| GREEN | 2000 | 1600 | 4000 | 3400 | 2800 | 2000 | 2,760 | 2,760 |