

ROUND SLING

SPECIFICATION FOR 50 TONNE - ORANGE

AS
4497.1



Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling.

Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank.

Conforms to Australian Standard AS 4497.1.

Black colour available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.

WLL 50,000KG

50000KG ORANGE		
CODE	LENGTH (M)	Wt. (kg)
905030	3.0	52.74
905040	4.0	70.3
905050	5.0	87.9
905060	6.0	105.5
905070	7.0	123.08
905080	8.0	140.7
905100	10.0	170



WORKING LOADING LIMIT CHART (KG)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
ORANGE	50000	40000	100000	86500	70500	50000	69,000	69,000