

# ROUND SLING

## SPECIFICATION FOR 8 TONNE - BLUE

AS  
4497.1



### Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling.

Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank.

Conforms to Australian Standard AS 4497.1.

Black colour available upon request.

### Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.



### WLL 8000KG

| WLL 8000KG BLUE |            |          |
|-----------------|------------|----------|
| CODE            | LENGTH (M) | Wt. (kg) |
| 900810          | 1.0        | 1.7      |
| 900815          | 1.5        | 2.4      |
| 900820          | 2.0        | 3.1      |
| 900825          | 2.5        | 4.1      |
| 900830          | 3.0        | 5.5      |
| 900835          | 3.5        | 5.4      |
| 900840          | 4.0        | 6.14     |
| 900845          | 4.5        | 6.94     |
| 900850          | 5.0        | 7.58     |
| 900855          | 5.5        | 8.33     |
| 900860          | 6.0        | 9.1      |
| 900880          | 8.0        | 13       |
| 900891          | 10.0       | 15.16    |

### WORKING LOAD LIMITS CHART (KG) - (WLLs)

| ROUND SLING |          |       |        |       |       |      |                        |                        |
|-------------|----------|-------|--------|-------|-------|------|------------------------|------------------------|
|             | VERTICAL | CHOKE | BASKET | 60°   | 90°   | 120° | SINGLE WRAP<br>Max 45° | DOUBLE WRAP<br>Max 45° |
| BLUE        | 8000     | 6400  | 16000  | 13600 | 11200 | 8000 | 11,040                 | 11,040                 |