

SPECIFICATIONS

Model	Cap Ton	Stroke (mm)	Oil Cap (cm ³)	Cylinder Effective Area (cm ²)	A Retracted Height (mm)	B Extended Height (mm)	C Outside Dia. (Ømm)	D Bore Dia. (Ømm)	E (Ømm)	F (mm)	G (mm)	H (mm)	I (ØUN)	J (mm)	L (mm)	M (ØUN)	N (mm)	Weight (kgs)
C51	5	25.4	16.2	6.47	110.2	135.6	38.1	28.7	25.4	19	25.4	6	¾"-16	14.2	14.2	1½"-16	28.7	1
C53		76.2	48.8	6.47	165.1	241.3	38.1	28.7	25.4	19	25.4	6	¾"-16	14.2	14.2	1½"-16	28.7	1.5
C55		127	81.8	6.47	215.9	342.9	38.1	28.7	25.4	19	25.4	6	¾"-16	14.2	14.2	1½"-16	28.7	1.9
C57		177.8	114	6.47	273.1	450.9	38.1	28.7	25.4	19	25.4	6	¾"-16	14.2	14.2	1½"-16	28.7	2.4
C59		231.9	148.6	6.47	323.94	555.8	38.1	28.7	25.4	19	25.4	6	¾"-16	14.2	14.2	1½"-16	28.7	2.8
C101	10	25.4	36.7	14.46	91.9	117.3	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	1.8
C102		54.1	77.8	14.46	121.4	175.5	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	2.3
C104		104.9	151.2	14.46	171.5	276.4	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	3.3
C106		155.7	224.5	14.46	247.7	403.4	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	4.5
C108		203.2	323	14.46	298.5	501.7	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	5.5
C1010		257.2	371	14.46	349.3	606.6	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	6.4
C1012		305.1	439.3	14.46	403.1	708.2	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	6.8
C1014		364.7	514.6	14.46	450.1	806.5	57.2	42.9	38.1	19	38.1	6	1"-8	19	12.7	2¼"-14	28.7	7.7
C151	15	26.5	63	23.76	124	150.5	73	55	40	19	38	10	1"-8	25.4	12.7	2¾"-16	30.2	3.3
C152		50.8	102.9	20.27	149.4	200.2	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	4.1
C154		101.6	206	20.27	200.2	301.8	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	5
C156		152.4	308.9	20.27	271.5	423.9	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	6.8
C158		203.2	411.8	20.27	322.3	525.5	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	8.2
C1510		254	514.9	20.27	373.1	627.1	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	9.5
C1512		304.8	617.8	20.27	423.9	728.7	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	10.9
C1514		355.6	720.7	20.27	474.7	830.3	69.9	50.8	41.4	24.9	39.9	10	1"-8	25.4	12.7	2¾"-16	30.2	11.8
C251	25	25.4	86	33.19	143.5	168.9	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	5.5
C252		50.8	169	33.19	165.1	215.9	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	6.4
C254		101.6	338	33.19	215.9	317.5	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	8.2
C256		158.7	528.2	33.19	273.1	431.8	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	10
C258		209.5	697.3	33.19	323.9	533.4	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	12.3
C2510		260.3	866.2	33.19	374.7	635	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	14.1
C2512		311.1	1035	33.19	425.5	736.6	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	16.4
C2514		361	1204	33.19	476.3	838.2	85.1	65	57.2	25.4	50.8	11	1½"-16	25.4	19.1	3⅝"-12	49.3	17.7
C552	55	50.8	362	71.34	176.3	227.1	127	95.3	79.5	35	80	3	-	-	19.1	5"-12	44.5	15
C554		101.1	724	71.34	227.6	328.7	127	95.3	79.5	35	80	3	-	-	19.1	5"-12	44.5	19.1
C556		158.8	1130	71.34	282.7	441.5	127	95.3	79.5	35	80	3	-	-	19.1	5"-12	44.5	23.2
C5510		254	1816	71.34	383.54	638.81	127	95.3	79.5	35	80	3	-	-	19.1	5"-12	44.5	29.5
C5513		336.6	2398	71.34	460.5	797.1	127	95.3	79.5	35	80	3	-	-	19.1	5"-12	44.5	37.7
C1002	100	58.3	708	133.36	219.2	272.5	174.5	130	104.9	39.9	104.9	3	-	-	25.4	6⅞"-12	44.5	43
C1006		167.4	2240	133.36	358.1	525.5	174.5	130	104.9	39.9	104.9	3	-	-	25.4	6⅞"-12	44.5	59.1
C10010		260.1	3465	133.36	449.6	709.7	174.5	130	104.9	39.9	104.9	3	-	-	25.4	6⅞"-12	44.5	72.7