

# FULL BODY HARNESS / HOT WORKS

## SPECIFICATION FOR 9150017

**1. Permanent Upright Dorsal D-ring:** Stamped Stainless Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN. Proof Load Tested.



**2. Adjustable Buckle:** provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



**3. Retrieval attachment confine space shoulder loops**


**4. Combination Buckle:** Stainless Steel, MBS 15kN



**5. Product Label:** with protection sleeve.

**6. Fall arrest & Retrieval attachment loops:** The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.

**7. Aramid Webbing:** Made with kevlar or equivalent core and aramid fibre outer covering. High heat aramid thread used to help keep welding and grinding sparks damage to a minimum.



<b>REF.</b>	9150017
<b>SIZES</b>	Standard = M-XL
<b>KG</b>	MAX. 140 KG (Instruction Manual - HLP-2021-V1.2)
<b>AS/NZS</b>	AS/NZS 1891.1:2020
<b>Attachment</b>	Dorsal D-Ring (A), Lower Sternal Webbing (A) - use both loops together
	2 / 3
<b>MAT.</b>	
<b>MAT.</b>	Aramid fibre heat resistant webbing
	<b>Not Fitted</b> Can be bought as an add on - 915075
<b>kg</b>	1.35 KG
	YES

**SIZES**




**KG**

Size Max. user weight



Number of adjustment buckles / Combination buckles



Confined Space Loops



Material of rings / buckles



Suspension Trauma Straps