

# Double Adjustable Lanyard - Double Action hook with Double Action Scaffold hooks

## SPECIFICATION FOR 916126



**Double Action Snap Hook:** made of forged alloy steel, MBS 23kN. Gate opening 20mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate




**Parking D-Ring:** made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish. ANSI Z359.12-2009 Used to park unused lanyard legs











**Integral energy shock absorber:** made of 44mm wide webbing and is shrink wrapped. it reduces the impact of a fall to less than 6kN.





**Double Action Scaffold Hook:** made of forged alloy steel, MBS 23kN, Gate opening 60mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate



**Adjuster Buckle:** made of forged alloy steel, MBS 15kN, with golden yellow galvanised finish. ANSI Z359.12-2009

REF.	916126		
AS/NZS	AS 1891.5:2020		
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1		
	60 kg's	Minimum Fall Clearance	5.3 m
	140 kg's	Minimum Fall Clearance	6.3 m
LG	Adjustable Length 1 m - 2 m		
MAT.	 44 mm ± 1mm Polyester		
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN		
	44 mm ± 1mm		
	PN 145 - ANSI Z359.12-2009  STEEL	2 x PN 140 - ANSI Z359.12-2009  STEEL	2 x PB 006 - ANSI Z359.12-2009  STEEL
	2.8 KG		

	<b>R (kN)</b>	/	<b>TOF (kN)</b>	/	<b>PDF</b>
Width of the energy absorber	<b>Static strength</b> (Static load applied to fully deployed lanyard)	/	<b>Tear out Force</b> (Force required to activate shock pack )	/	<b>Peak deceleration Force</b> (Maximum force applied to user during shock pack functioning)
	<b>Harness connector / Anchor connector / Adjuster / Parking D-Ring</b>				