


Double Elasticated Lanyard - Triple Action Hooks

SPECIFICATION FOR 916121










Triple Action Locking Snap Hook: made of forged alloy steel, MBS 23kN. Gate opening 19.5mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate





Parking D-Ring: made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish. ANSI Z359.12-2009 Used to park unused lanyard legs



Integral energy shock absorber:: made of 44mm wide webbing and is shrink wrapped. it reduces the impact of a fall to less than 6kN.

REF.	916121		
AS/NZS	AS 1891.5:2020		
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1		
	60 kg's	Minimum Fall Clearance	5.3 m
	140 kg's	Minimum Fall Clearance	6.3 m
LG	Length 2m		
MAT.	Polyester	44 mm ± 1mm	
		 PES	
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN		
	44 mm ± 1mm		
	PN 152AT - ANSI Z359.12-2009	 2 x PN 152AT - ANSI Z359.12-2009	 DR 008 - ANSI Z359.12-2009
	1.5 KG		

 Width of the energy absorber	R (kN) Static strength (Static load applied to fully deployed lanyard)	/	TOF (kN) Tear out Force (Force required to activate shock pack)	/	PDF Peak deceleration Force (Maximum force applied to user during shock pack functioning)
 Harness connector / Anchor connector / Parking D-Ring					