

Double Elasticated Lanyard - Triple Action hook and Double Action Scaffold Hooks

SPECIFICATION FOR 916123



Triple Action Locking Snap Hook: made of forged alloy steel, MBS 23kN. Gate opening 19.5mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate










Parking D-Ring: made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish. ANSI Z359.12-2009 Used to park unused lanyard legs





Integral energy shock absorber: made of 44mm wide webbing and is shrink wrapped. it reduces the impact of a fall to less than 6kN.



Double Action Scaffold Hook: made of forged alloy steel, MBS 23kN, Gate opening 60mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate

REF.	916123			
AS/NZS	AS 1891.5:2020			
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1			
	60 kg's	Minimum Fall Clearance	5.3 m	
	140 kg's	Minimum Fall Clearance	6.3 m	
LG	Length 2m			
MAT.	Polyester 44 mm ± 1mm  PES			
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN			
	44 mm ± 1mm			
	PN 152AT - ANSI Z359.12-2009		2 x PN 140 - ANSI Z359.12-2009	 DR 008 - ANSI Z359.12-2009
	2.7 KG			

	R (kN)	/	TOF (kN)	/	PDF
Width of the energy absorber	Static strength (Static load applied to fully deployed lanyard)	/	Tear out Force (Force required to activate shock pack)	/	Peak deceleration Force (Maximum force applied to user during shock pack functioning)
					
Harness connector / Anchor connector / Parking D-Ring					