


Double Lanyard - Triple Action Hooks

SPECIFICATION FOR 916120



Triple Action Locking Snap Hook:

made of forged alloy steel, MBS 23kN.
Gate opening 19.5mm, with golden yellow galvanised finish.
ANSI Z359.12-2009 - 16kN gate










Parking D-Ring:

made of forged alloy steel, MBS 23kN, with golden yellow galvanised finish. ANSI Z359.12-2009
Used to park unused lanyard legs



Integral energy shock absorber::

made of 44mm wide webbing and is shrink wrapped. it reduces the impact of a fall to less than 6kN.

REF.	916120					
AS/NZS	AS 1891.5:2020					
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1					
	60 kg's	Minimum Fall Clearance	5.3 m			
	140 kg's	Minimum Fall Clearance	6.3 m			
LG	Length 2m					
MAT.	 44 mm ± 1mm Polyester					
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN					
	44 mm ± 1mm					
	PN 152AT - ANSI Z359.12-2009		2 x PN 152AT - ANSI Z359.12-2009		DR 008 - ANSI Z359.12-2009	
	1.46 KG					


Width of the energy absorber

R (kN) /
Static strength /
(Static load applied to fully
deployed lanyard)

TOF (kN) /
Tear out Force /
(Force required to activate
shock pack)

PDF /
Peak deceleration Force /
(Maximum force applied to user
during shock pack functioning)

 /  / 
Harness connector / Anchor connector / Parking D-Ring