

# Adjustable Lanyard Single with Scaffold Hook

## SPECIFICATION FOR 916111



**Double Action Snap Hook:** made of forged alloy steel, MBS 23kN. Gate opening 20mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate




**Abrasion Resistant Covering:** prevents the webbing from being damaged by metallic contact of the connector.










**Integral energy shock absorber:** made of 44mm wide webbing and is shrink wrapped. It reduces the impact of fall to less than 6kN.



**Double Action Scaffold Hook:** made of forged alloy steel, MBS 23kN, Gate opening 60mm, with golden yellow galvanised finish. ANSI Z359.12-2009 - 16kN gate



**Adjuster Buckle:** made of forged alloy steel, MBS 15kN, with golden yellow galvanised finish. ANSI Z359.12-2009

REF.	916111		
AS/NZS	AS 1891.5:2020		
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1		
	60 kg's	Minimum Fall Clearance	5.3 m
	140 kg's	Minimum Fall Clearance	6.3 m
LG	Adjustable Length 1 m - 2 m		
MAT.	 44 mm ± 1mm Polyester		
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN		
	44 mm ± 1mm		
	PN 145 - ANSI Z359.12-2009		PN 140 - ANSI Z359.12-2009
			 PB 006 - ANSI Z359.12-2009
	1.25 KG		

  
Width of the energy absorber

**R (kN)**  
/ **Static strength**  
(Static load applied to fully deployed lanyard)

**TOF (kN)**  
/ **Tear out Force**  
(Force required to activate shock pack)

**PDF**  
/ **Peak deceleration Force**  
(Maximum force applied to user during shock pack functioning)

  
Harness connector / Anchor connector / Adjuster