

Lanyard Single - Triple Action

SPECIFICATION FOR 916105



Triple Action Locking Snap Hook:







made of forged alloy steel, MBS 23kN. Gate opening 19.5mm, with golden yellow galvanised finish. ANSIZ359.12-2009 - 16kN gate



Abrasion Resistant Covering: prevents the webbing from being damaged by metallic contact of the connector.



Integral energy shock absorber: made of 44mm wide webbing and is shrink wrapped. It reduces the impact of fall to less than 6kN.

REF.	916105		
AS/NZS	AS 1891.5:2020		
 Number of users Min user weight / Clearance Max user weight / Clearance	X 1		
	60 kg's	Minimum Fall Clearance	5.3 m
	140 kg's	Minimum Fall Clearance	6.3 m
LG	Length 2m		
MAT.	 44 mm ± 1mm Polyester		
R (kN) / TOF (kN) / PDF (kN)	12 kN / ≥ 2kN / ≤ 6kN		
	44 mm ± 1mm		
	PN 152AT- ANSI Z359.12-2009		PN 152AT - ANSI Z359.12-2009
	1.21 KG		


 Width of the energy absorber

R (kN) /
Static strength
 (Static load applied to fully
 deployed lanyard)

TOF (kN) /
Tear out Force
 (Force required to activate
 shock pack)

PDF
Peak deceleration Force
 (Maximum force applied to user
 during shock pack functioning)


 Harness connector / Anchor connector