

FULL BODY HARNESS CROSSOVER

SPECIFICATION FOR 915004



Permanent Upright Dorsal D-ring: Stamped Alloy Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN, Proof Load Tested.



Combination Buckle: Stamped Alloy Steel, MBS 15kN



Adjustable Buckle: provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



Product Label: with protection sleeve.



Chest D-ring: Made of forged alloy steel, MBS 23kN, Proof Load Tested. Inner Bar protects the webbing from being damaged by metallic contact.



Elastic Loops: Designed to retain the excess strap while adjustment.

REF.	915004
SIZES	Standard = M-XL
KG	MAX. 140 KG (Instruction Manual - HLP-2021-V1.2)
AS/NZS	AS/NZS 1891.1:2020
Attachment	Dorsal D-Ring (A), Sternal D-Ring (A)
	2 / 2
MAT.	STEEL
MAT. 45 mm	Polyester
	Not Fitted Can be bought as an add on - 915075
kg	1.20 KG
	NO

SIZES



KG

Size Max. user weight



Number of adjustment buckles / Combination buckles



Confined Space Loops



Material of rings / buckles



Suspension Trauma Straps