

FULL BODY HARNESS (AP) / SUSPENSION

SPECIFICATION FOR 915012

- 1. Dorsal D-ring: Made of Aluminium Alloy.
- 2. Frontal D-rings: Made of Aluminium Alloy.
- 3. Lateral D-rings: Made of Aluminium Alloy. Made of aluminium alloy. Designed with a bend to stand out enables easy attachment.
- 4. Fall arrest & Confine Space Shoulder Loops
- 5. Tool holding loops with Protective Cover
- 6. Padded Shoulder Strap: Fully padded with knitted mesh for better comfort and air circulation. Equipped with silver reflective tap.
- 7. Work Positioning Belt: Fully padded with mesh pads for better comfort and air circulation. Equipped with aluminium adjustable buckles.



8. Padded Thigh Strap: The distinctively placed fully padded straps with Quick release buckles allows easy adjustment. The knitted mesh net used in the pads maintains proper air circulation.

- 9. Adjustable Buckle: Provided with pulling grip strap to easily adjust straps for a good lift.
- 10. Ouick Release Buckle: Extremely easy to use with single-hand. Made of aluminium alloy.
- 11. Triple Action Karabiner: Light weight and easy to use. Made of aluminium alloy.
- Adjustable Seat Configuration Strap: Specially designed and provided with pulling grip strap to easily adjust straps to meet all purposes and provide better support than others.

915012 REF.

SIZES



Standard = M-XL

MAX. 140 KG

(Instruction Manaual - HLPM-2021-V1.2)

AS/NZS AS/NZS 1891.1:2020

Attachment Dorsal (A), Sternal (A), Lower Sternal (A), Pole Strap (PSA)

7 / 3









Polyester





N/A



2.10 KG



YES

SIZES





Number of adjustment buckles / automatic buckles



MAT. Material of rings / buckles



Suspension Trauma Straps

Size Max. user weight