

FULL BODY HARNESS

SPECIFICATION FOR 915001



Permanent Upright Dorsal D-ring: Stamped Alloy Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN, Proof Load Tested.



Combination Buckle: Stamped Alloy Steel, MBS 15kN



Adjustable Buckle: provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



Product Label: with protection sleeve.



Fall arrest & Retrieval attachment loops: The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.



Elastic Loops: Designed to retain the excess strap while adjustment.

REF.	915001
-------------	--------

SIZES	Standard = M-XL
KG	MAX. 140 KG (Instruction Manual - HLP-2021-V1.2)

AS/NZS	AS/NZS 1891.1:2020
---------------	--------------------

Attachment	Dorsal D-Ring(A), Sternal Webbing (A) - use both loops together
-------------------	---

	2 / 3
--	-------

MAT.	
-------------	--

MAT. 45 mm	Polyester
-------------------	-----------

	Not Fitted Can be bought as an add on - 915075
--	--

kg	1.20 KG
-----------	---------

	NO
--	----

SIZES		Confined Space Loops	MAT.	Material of rings / buckles	
KG	Number of adjustment buckles / Combination buckles				Suspension Trauma Straps

Size Max. user weight