

01 Height Safety Lifting Load Control Safety Management **HORIZONTAL SAFETY LINES** Technical Data Sheet



3400 Series Horizontal Safety Lines

These webbing safety lines give lateral and versatile continuous anchorage connections. The standard 3400 connection is made directly to the webbing line via a large hook or karabiner while the 3400UK features connection D rings.

Preferred methods of attaching the horizontal lifeline to a structure can include the following:

- Round slings exceeding 22kN in ultimate strength
- Flat slings exceeding 22kN in ultimate strength
- Wire slings exceeding 22kN in ultimate strength
- Karabiners exceeding 50kN in ultimate strength

- Safety shackles exceeding 22kN in ultimate strength
- Grade 80 self locking lifting hooks exceeding 22kN in ultimate strength
- Anchor points must have a minimum rating of 22kN
- 3400 Series horizontal lifelines have a maximum span of 18 metres.

- With the patented Tension Force Indicator (TFI), you can verify the pretension force in the system quickly and easily. When the jaws of the TFI are closed, it indicates the maximum pretensioning force that can be achieved of 750 daN.



Code	Length	Rating	Ratchet	Tension Force Indicator
3400	18m	1 Person	Standard	No
3400UK	18m	2 Person	20020 ABS	Yes

3400UK



3400

