



6000 Rigger's Kit

1100 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3055 Lanyard with Scaffold Hook

x 1



- Single leg lanyard
- Webbing construction
- 1.8 metres in length
- Fitted with H1 snap hook and H3 scaffold hook
- 1320g with fittings
- 100kg maximum load capacity
- AS/NZS 1891.1 certified

E 2000

x 2



- High tenacity polyester webbing construction
- Designed to be used in a reeved configuration
- 15kN maximum fall arrest load
- 2m maximum fall

3400 Safety Line

x 1



- High tenacity polyester webbing construction
- Connects directly to the webbing with a large hook
- 18 metres long
- Single person use
- Standard ratchet

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying

3.25t Safety Shackles

x 2



- 3.25 tonne safe working load
- 27mm jaw width
- 19mm pin diameter
- 79mm working width

K2 Karabiner

x 2



- Alloy steel oval karabiner
- Screw gate type with a 1kN gate strength
- 15mm gate opening
- 25kN maximum strength
- 157g weight

6001 Roofer's Kit

1104 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Rear fall arrest extension strap
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3053 Lanyard

x 1



- Single leg lanyard
- Webbing construction
- 1.8 metres in length
- Fitted with two H1 snap hooks
- 945g with fittings
- 100kg maximum load capacity
- AS/NZS 1891.1 certified

3108 Fall Arrest Anchorage Line

x 1



- Designed for horizontal use
- 11mm rope diameter; 15m length
- RF1 Type 1 adjuster with maximum capacity of 15kN
- H1 double action safety hook with a maximum capacity of 25kN

3501 Anchor Sling

x 1



- Webbing construction
- Choke or basket use
- 22kN (choke) maximum capacity
- Connects to D ring
- 1.3 metres long

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying

K2 Karabiner

x 1



- Alloy steel oval karabiner
- Screw gate type with a 1kN gate strength
- 15mm gate opening
- 25kN maximum strength
- 157g weight

6001SA Roofer's Kit

1104 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3108SA Fall Arrest Anchorage Line

x 1



- Designed for horizontal use
- 15 metre long kernmantle with an 11mm rope diameter
- RF1 Type 1 adjuster with maximum capacity of 15kN
- Tear webbing shock absorber with a maximum fall capacity of 2-6kN
- H1 double action safety hook with a maximum capacity of 25kN

3501 Anchor Sling

x 1



- Webbing construction
- Choke or basket use
- 22kN (choke) maximum capacity
- Connects to D ring
- 1.3 metres long

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying

K2 Karabiner

x 1



- Alloy steel oval karabiner
- Screw gate type with a 1kN gate strength
- 15mm gate opening
- 25kN maximum strength
- 157g weight

6002 Basic Kit

1100 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3053 Lanyard

x 1



- Single leg lanyard
- Webbing construction
- 1.8 metres in length
- Fitted with two H1 snap hooks
- 945g with fittings
- 100kg maximum load capacity
- AS/NZS 1891.1 certified

3501 Anchor Sling

x 1



- Webbing construction
- Choke or basket use
- 22kN (choke) maximum capacity
- Connects to D ring
- 1.3 metres long

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying

60020P Order Picker's Kit

1100 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3201 Retracting Lanyard with Triple Action Karabiners

x 1



- Lightweight retracting lanyard with a sturdy steel and plastic housing
- 1.25kg weight
- 2.25 metres long with 50mm webbing
- Overall size of 240mm x 110mm x 75mm

K2 Karabiner

x 1



- Alloy steel oval karabiner
- Screw gate type with a 1kN gate strength
- 15mm gate opening
- 25kN maximum strength
- 157g weight

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying

6008 All Purpose Kit

1104 ERGO Safety Harness

x1



- 25mm high tenacity polyester
- Breathable rear mesh panel
- Confined space attachment loops
- Hardened steel alloy fittings
- Suspension trauma relief straps
- Original ERGO Euro style geometry
- Multi layer, reinforced redundant backup design at rear D
- Load bearing straps protected from abrasion by outer layer straps at rear D
- 3 layer pocket webbing supporting load bearing
- Chest strap for front D
- Ergonomic, pull down adjustment at front shoulder and leg straps
- Sub-pelvic strap to minimise peel out
- Fully adjustable shoulder, leg and chest straps
- Leg straps fixed at hips – no excessive tightening around thighs in the event of an arrested fall
- Open slots on sides at hip for riggers and accessory belts
- Front D allows for easier attachment with remote rescue kits
- Colour contrasted for ease of identification
- Suitable for confined space entry, construction, elevated work platforms, fall arrest, ladder systems, maintenance and roof work
- Minimum tensile strength 15kN as per AS 1891.1 certification

3055 Lanyard with Scaffold Hook

x 1



- Single leg lanyard
- Webbing construction
- 1.8 metres in length
- Fitted with H1 Snap Hook and H3 Scaffold Hook
- 1320g with fittings
- 100kg maximum load capacity
- AS/NZS 1891.1 certified

3051 Shock Absorber

x1



- Tear webbing
- Maximum fall capacity of 2-6kN
- Polyester construction
- AS/NZS 1891.1 certified

3108 Fall Arrest Anchorage Line

x 1



- Designed for horizontal use
- 15 metre long kernmantle with an 11mm rope diameter
- RF1 Type 1 adjuster with maximum capacity of 15kN
- H1 double action safety hook with a maximum capacity of 25kN

3501 Anchor Sling

x 1



- Webbing construction
- Choke or basket use
- 22kN (choke) maximum capacity
- Connects to D ring
- 1.3 metres long

Kit Bag

x 1



- Toughened polyester construction
- 500 x 250 x 250mm
- Top opening double fitted zip
- Velcro handle wrap for easy carrying