

## CSA Certified Titan Stretch Pack Type Shock Absorbing Lanyards

### Description

Titan Stretch lanyards combine the integral SofStop® shock absorber with a unique stretchable lanyard design.

### Materials

Webbing:

- Safety Strap: Type 7 webbing
  - Safety Jacket: Tubular polyester
- Thread: Polyester  
SofStop Cover: Vinyl  
Hardware: Steel  
Locking Snap Hooks: 5,000 lb. (22kN)

\* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

### Technical

- CSA Approved  
Max. Capacity Range: 120-335 lbs. (141 kg)  
Maximum Elongation Distance: 52 in. (in a 6 ft. drop)  
*Non CSA Approved*  
Max. Capacity Range: 100-385 lbs. (175 kg)  
Maximum Elongation Distance: 68 in. (in a 6 ft. drop)  
Snap Hooks: 5,000 lbs. (22kN)  
3/4" (19mm) gate opening  
Rebar Hooks: 5,000 lbs. (22kN)  
2 1/2 in. (63mm) gate opening  
Fall Arrest Force: 1,800 lbs. max.

See table on product for specific weight range and elongation distances.

Model Number	Color	Number of Legs	Harness Connection	Anchorage Connection	Lanyard Length
T1SSSR-US6C	Orange	One	Stamped Snap Hook	Stamped Rebar	6 ft. (1.8 m)
T1SSSS-US6C	Orange	One	Stamped Snap Hook	Stamped Snap Hook	6 ft. (1.8 m)
T2SSSR-US6C	Orange	Two	Stamped Snap Hook	Stamped Rebar	6 ft. (1.8 m)



T1SSSS-US6C

### Certification

Meets all CSA Z259.11-17 requirements.

**⚠** This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.