

# FULL BODY HARNESS

## SPECIFICATION FOR 915002QR



**Permanent Upright Dorsal D-ring:** Stamped Alloy Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN, Proof Load Tested.



**Quick Release Buckle:** Extremely easy to use with single hand. Designed with lock indicator. Made of stamped alloy steel, MBS: 15kN.



**Adjustable Buckle:** provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



**Snap Hook:** Made of forged Alloy Steel, Double Action, MBS 23kN, 20mm Opening, with thumb and easy to adjust straps for a good lift.



**Product Label:** with protection sleeve.



**Fall arrest & Retrieval attachment loops:** The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.



**Elastic Loops:** Designed to retain the excess strap while adjustment.



**Abrasion Resistant Covering:** prevents the webbing from being damaged by metallic contact of the connector.



**Energy Absorber:** The special webbing inside the energy absorber takes up most of the shock when a fall occurs.

REF.	915002QR
------	----------

SIZES	Standard = M-XL
KG	MAX. 140 KG (Instruction Manual - HLP-2021-V1.2)

AS/NZS	Harness - AS/NZS 1891.1:2020 / Lanyard - AS 1891.5:2020
--------	---

Attachment	Dorsal D-Ring - Lanyard attached (A), Sternal Webbing (A) - use both loops together
------------	---

	2 / 3
--	-------

MAT.	
------	--

MAT.  45 mm	Polyester
-------------	-----------

	<b>Not Fitted</b> Can be bought as an add on - 915075
--	--

	1.95 KG
--	---------

	NO
--	----

SIZES			MAT.	
KG	Number of adjustment buckles / automatic buckles	Confined Space Loops	Material of rings / buckles	Suspension Trauma Straps

Size Max. user weight