




Oblong Master Links and Multi Master Link with Flattened Section

cromox Oblong Master Link CAGF. Grade 60 for 1- and 2-leg chain slings. sand blasted. AISI 318LN (2205 Duplex)

These master links have a flattened section to allow the use of connectors (e.g. clevis shackles type CGS) and wire rope thimbles.

Type	W.L.L.		for Chain		Dimensions mm			Weight kg
	t		1 – leg	2 – leg 90°	d	t	b	
KW-CAGF10	0.63		5	4	10	80	50	0.150
KW-CAGF13	1.55		6/7/8	5/6	13	110	60	0.340
KW-CAGF16	2.45		10	7/8	16	110	60	0.530
KW-CAGF18	3.55		–	10	18	135	75	0.800
KW-CAGF22	6.00		13/16	13	22	160	90	1.500
KW-CAGF26	8.00		18	16	26	180	100	2.300
KW-CAGF32	12.00		20	18	32	200	110	3.900
*KW-CAGF36	16.00		–	20	36	260	140	6.350

*Not stocked. Available on Request.




cromox Multi Master Link CAKF. Grade 60 for 3- and 4-leg chain slings. sand blasted. AISI 318LN (2205 Duplex)

These master links have a flattened section to allow the use of connectors (e.g. clevis shackles type CGS) and wire rope thimbles.

Type	W.L.L.		for Chain	Dimensions mm			Weight kg
	90°	120°		d	t	b	
*CAKF13/10	1.30	0.90	5	A 13 B 10	110 44	60 25	0.520
KW-CAKF16/13	2.65	1.85	6	A 16 B 13	110 54	60 25	0.970
KW-CAKF18/16	3.25	2.30	7/8	A 18 B 16	135 70	75 34	1.600
KW-CAKF22/16	5.15	3.65	10	A 22 B 18	160 85	90 40	2.760
*CAKF26/22	8.15	5.75	13	A 26 B 22	180 115	100 50	4.450
*CAKF32/26	12.60	9.00	16	A 32 B 26	200 140	110 65	7.550

*Not stocked. Available on request.



cromox Multi Master Link NAKF. Grade 50 for 3- and 4-leg chain slings. sand blasted

Type	W.L.L.		for Chain	Dimensions mm			Weight kg
	90°	120°		d	t	b	
KW-178622BK	1.70	1.25	8	A 22 B 16	160 70	90 34	2.300
KW-178626BK	2.80	2.00	10	A 26 B 18	180 85	100 40	3.560

