


Connectors & Shackles

cromox Clevis Shackles CGS. Grade 60 tested. sand blasted

	Type	W.L.L.	Dimensions mm			Weight
		t	t	b	a	kg
NEW	KW-CGS04	0.40	19.0	15	6.5	0.060
NEW	KW-CGS05	0.63	21.0	17	7.0	0.072
	KW-CGS06	0.90	26.0	20	7.0	0.160
	KW-CGS08	1.55	30.0	23	9.0	0.230
	KW-CGS10	2.45	40.0	28	11.0	0.460
	KW-CGS13	3.85	48.0	38	14.0	0.675
	KW-CGS16	6.00	53.0	42	17.0	1.200
NEW	*CGS18	8.00	61.5	48	19.5	1.850


*Not stocked. Available on Request.



cromox Connecting Links. CVG. Grade 60 tested. sand blasted

	Type	W.L.L.	Dimensions mm			Weight
		t	t	b	d	kg
	KW-CVG06	0.90	42	15	7.5	0.085
	*CVG07	1.25	42	15	9.5	0.090
	KW-CVG08	1.55	55	18	11.5	0.150
	KW-CVG10	2.45	69	22	14.50	0.310
NEW	KW-CVG13	3.85	75	29	15.0	0.515
NEW	KW-CVG16	6.00	92	36	18.5	0.980


*Not stocked.



Part	Material
Body & Bolt	AISI 318LN
Safety Pin & Spring	AISI 301

cromox D-Shackles CSA. Grade 60 tested. bright polished. AISI 316

Type	W.L.L.	Dimensions mm				Weight
	t	a	d	t	b	kg
KW-CSA04	0.40	7	6	23	12	0.035
KW-CSA05	0.63	9	8	24	17	0.070
KW-CSA06	0.90	11	10	35	20	0.135
KW-CSA08	1.55	13	12	42	25	0.220
KW-CSA10	2.45	18	16	64	32	0.510
KW-CSA13	3.85	21	19	76	38	0.910
PE-PH5TA	5.00	19	16	64	32	0.550
PE-PH7TA	7.00	22	19	76	38	1.000
PE-PH9TA	9.00	26	22	88	44	1.900
PE-PH11TA	11.00	29	25	102	51	2.900
PE-PH13TA	13.00	32	29	114	57	3.100



cromox Safety D-Shackles CSS. Grade 60 tested. bright polished

Type	W.L.L.	Dimensions mm				Weight
	t	a	d	t	b	kg
KW-CSS04	0.40	7	6	23	12	0.035
KW-CSS05	0.63	9	8	24	17	0.070
KW-CSS06	0.90	11	10	35	20	0.135
KW-CSS08	1.55	13	12	42	25	0.225
KW-CSS10	2.45	18	16	64	32	0.540
KW-CSS13	3.85	21	19	76	38	0.945

