


Hooks. Self Locking and Safety Sling.

cromox Clevis Hooks CGHF. Grade 60
with safety latch. sand blasted

Type	W.L.L.	Dimensions mm			Weight
	t	t	g	h	kg
KW-CGHF 05	0.63	78	25	22	0.400
KW-CGHF 06	0.90	78	25	22	0.400
KW-CGHF07/08	1.55	97	32	28	0.760
KW-CGHF10	2.45	121	40	34	1.440
*KW-176613GB	3.20	143	48	47	2.600
*KW-176616GB	5.00	180	69	57	4.900


*Discontinued Lines



cromox Eye Hooks COHF. Grade 60
with safety latch. sand blasted

Type	W.L.L.	Dimensions mm				Weight
	t	t	g	b	h	kg
KW-COHF 04	0.40	75	20	17	17	0.185
KW-COHF05/06	0.90	100	25	25	22	0.350
KW-COHF07/08	1.55	126	32	27	28	0.790
KW-COHF10	2.45	160	40	37	34	1.370
KW-COHF13	3.85	190	51	48	45	3.000
*COHF 16	6.00	230	66	55	51	4.800
*COHF 18	8.00	255	70	65	56	6.400

*Not stocked. Available on Request.



cromox Self Locking Clevis Hooks CGSL. Grade 60
similar to DIN EN 1677-3. sand blasted

Type	W.L.L.	Dimensions mm			Weight
	t	t	g	h	kg
KW-CGSL05	0.63	83	28	19	0.280
KW-CGSL06	0.90	96	33	22	0.440
*CGSL07	1.25	109	37	25	0.640
KW-CGSL08	1.55	122	41	28	0.880
KW-CGSL10	2.45	148	50	34	1.600

*Not stocked. Available on Request.



cromox Self Locking Eye Hooks COSL. Grade 60
similar to DIN EN 1677-3. sand blasted

Type	W.L.L.	Dimensions mm				Weight
	t	t	g	b	h	kg
KW-COSL05	0.63	93	28	24	19	0.270
KW-COSL06	0.90	108	33	25	22	0.410
KW-COSL07	1.25	122	37	27	25	0.600
KW-COSL08	1.55	137	41	28	28	0.850
KW-COSL10	2.45	166	50	38	34	1.500
KW-COSL13	3.85	220	66	48	45	3.500
*COSL16	6.00	250	75	56	51	5.100

*Not stocked. Available on Request.



Part	Material
Body	AISI 318LN
Safety Latch	AISI 318LN
Spring	AISI 301
Bolt	AISI 318LN
Safety Pin	AISI 301

Advantages:

- Bionic Design - high WLL at favourable piece weight.
- Exchangeable safety mechanism.
- Best corrosion resistance through offshore approved materials entirely in stainless steel.