


Swivel Load Hooks and Spare Parts

cromox Swivel Load Hooks with eyelet CWHB. Grade 60 blasted

Type	W.L.L.	Dimensions mm				Weight
	t	t	g	b	h	kg
CWHB 4/5	0.63	120	20	40	16.0	0.650
CWHB 6/7	1.25	165	25	49	21.0	0.988
CWHB 8/10	2.50	235	40	64	33.0	2.710



Advantages:

- Duplex material 1.4462 (AISI 318LN) ensures superior corrosion resistance
- Ball bearings allow easy rotation even under full load
- Large eyelet dimensions for multiple applications
- Bionic design guarantees high admissible loads
- Flattened section on the eyelet enables combination with cromox Clevis Shackles CGS

Part	Material
Body	AISI 318LN
Safety Latch	AISI 318LN
Bolt	AISI 318LN
Safety Pin	AISI 301
Bracket	AISI 318LN
Nut	AISI 318LN
Washer	AISI 318LN
Ball Bearings	AISI 440C

cromox Safety Latch Assembly CSG for CGHF & COHF. sand -blasted

Type	Weight
	kg
CSG 04	0.026
CSG 05/06	0.030
CSG 07/08	0.050
CSG 10	0.095
CSG 13	0.150
CSG 16	0.250
CSG 18	0.250



cromox Bolts and Pins CBP for CGHF & CGS. bright polished

Type	Dimensions mm	Weight
	d/l	kg
CBP 05	6 x 28	0.007
CBP 06	8 x 28	0.010
CBP 07	8 x 32	0.013
CBP 08	10 x 32	0.020
CBP 10	13 x 40	0.045
CBP 13	16 x 45	0.070
CBP 16	20 x 55	0.140



Heavy-duty hook constructed with an integrated safety latch.

The latch itself is highly resistant to side buckling. If the hook becomes overloaded the latch will disengage.

The hook point is designed to prevent usage with the incorrect chain size while ensuring that the safety latch does not reduce hook admittance.