



# Lifting & Hoisting

Chain Blocks

## 16t Heavy Weight Chain Block

Integrating safety, durability and innovation, our 16t chain block provides reliable lifting in the most demanding industrial environments whilst ensuring operator safety. Lift, position and pull virtually any angle – even in confined spaces.

Capacity:

16.0t

### Applications:

Agriculture, Construction, Engineering, Infrastructure, Logistics, Manufacturing, Mining, Ports, Utilities.

Complies with:

AS/NZS1418

#### **Product Features**

- Factory tested to 1.5 x W.L.L.
- Super strength zinc plated alloy load chain.
- Lower hook complete with thrust race bearing.
- Fully machined lift wheel, supported by needle roller bearings.
- Weather protected automatic Weston brake with unique Twin Pawls.





## **PRODUCT INFORMATION**






# Lifting & Hoisting

Chain Blocks

### SPECIFICATIONS

PRODUCT CODE	WORKING LOAD LIMIT (W.L.L.)	STANDARD LIFT	FALLS OF CHAIN	HAND EFFORT TO LIFT W.L.L.	LOAD CHAIN Ø	NET WEIGHT
CBOZ160-3	16.0t	3m	6	36kg	10mm	160.0kg
CBOZ160-3	16.0t	6m	6	36kg	10mm	221.2kg





## DIMENSIONS

PRODUCT CODE	WORKING LOAD LIMIT (W.L.L.)	A	В	С	D	E	F	Hmin
CBOZ160-3	16.0t	441mm	120mm	78mm	400mm	222mm	110mm	1094mm
CBOZ160-3	16.0t	441mm	120mm	78mm	400mm	222mm	110mm	1094mm

